

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sodium Selenite / Vitamin E Injection Formulation

Version 6.0 Revision Date: 11/29/2023 SDS Number: 895430-00016 Date of last issue: 09/30/2023
Date of first issue: 09/21/2016

SECTION 1. IDENTIFICATION

Product name : Sodium Selenite / Vitamin E Injection Formulation
Other means of identification : E-SE Injection (A000603)

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc
Address : 126 E. Lincoln Avenue
Rahway, New Jersey U.S.A. 07065
Telephone : 908-740-4000
Emergency telephone : 1-908-423-6000
E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity (Oral) : Category 4
Acute toxicity (Inhalation) : Category 4
Skin sensitization : Category 1
Specific target organ toxicity : Category 1
- repeated exposure

GHS label elements

Hazard pictograms :

Signal Word : Danger

Hazard Statements : H302 + H332 Harmful if swallowed or if inhaled.
H317 May cause an allergic skin reaction.
H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sodium Selenite / Vitamin E Injection Formulation

Version 6.0 Revision Date: 11/29/2023 SDS Number: 895430-00016 Date of last issue: 09/30/2023
Date of first issue: 09/21/2016

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a doctor if you feel unwell. Rinse mouth.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.

P314 Get medical attention if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical attention.

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
(dl)-a-Tocopheryl acetate	7695-91-2	5.15
Benzyl alcohol	100-51-6	2.19
Sodium selenite	10102-18-8	0.35 - 1.13

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sodium Selenite / Vitamin E Injection Formulation

Version 6.0 Revision Date: 11/29/2023 SDS Number: 895430-00016 Date of last issue: 09/30/2023
Date of first issue: 09/21/2016

- If swallowed : If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.
Get medical attention.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : Harmful if swallowed or if inhaled.
May cause an allergic skin reaction.
Causes damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material
-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sodium Selenite / Vitamin E Injection Formulation

Version 6.0 Revision Date: 11/29/2023 SDS Number: 895430-00016 Date of last issue: 09/30/2023
Date of first issue: 09/21/2016

can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Do not breathe mist or vapors.
Do not swallow.
Avoid contact with eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Explosives
Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
(dl)-a-Tocopheryl acetate	7695-91-2	TWA	5000 ug/m3 (OEB 1)	Internal
Benzyl alcohol	100-51-6	TWA	10 ppm	US WEEL
Sodium selenite	10102-18-8	TWA	20 µg/m3 (OEB 3)	Internal

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sodium Selenite / Vitamin E Injection Formulation

Version 6.0 Revision Date: 11/29/2023 SDS Number: 895430-00016 Date of last issue: 09/30/2023
Date of first issue: 09/21/2016

		Wipe limit	200 µg/100 cm ²	Internal
		TWA	0.2 mg/m ³ (selenium)	OSHA Z-1
		TWA	0.2 mg/m ³ (selenium)	ACGIH
		TWA	0.2 mg/m ³ (selenium)	NIOSH REL

Engineering measures : Use appropriate engineering controls and manufacturing technologies to control airborne concentrations (e.g., drip-less quick connections).
All engineering controls should be implemented by facility design and operated in accordance with GMP principles to protect products, workers, and the environment.
Containment technologies suitable for controlling compounds are required to control at source and to prevent migration of the compound to uncontrolled areas (e.g., open-face containment devices).
Minimize open handling.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Consider double gloving.

Eye protection : Wear safety glasses with side shields or goggles.
If the work environment or activity involves dusty conditions, mists or aerosols, wear the appropriate goggles.
Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or aerosols.

Skin and body protection : Work uniform or laboratory coat.
Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces.
Use appropriate degowning techniques to remove potentially contaminated clothing.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sodium Selenite / Vitamin E Injection Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/30/2023
6.0	11/29/2023	895430-00016	Date of first issue: 09/21/2016

working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.
The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the use of administrative controls.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aqueous solution
Color	: amber
Odor	: No data available
Odor Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available
Flash point	: No data available
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Flammability (liquids)	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: No data available
Relative vapor density	: No data available
Relative density	: No data available
Density	: No data available
Solubility(ies) Water solubility	: No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sodium Selenite / Vitamin E Injection Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/30/2023
6.0	11/29/2023	895430-00016	Date of first issue: 09/21/2016

Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Can react with strong oxidizing agents.
Conditions to avoid	:	None known.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Harmful if swallowed or if inhaled.

Product:

Acute oral toxicity	:	Acute toxicity estimate: 422.35 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: 4.33 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method

Components:

(dl)-a-Tocopheryl acetate:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sodium Selenite / Vitamin E Injection Formulation

Version 6.0 Revision Date: 11/29/2023 SDS Number: 895430-00016 Date of last issue: 09/30/2023
Date of first issue: 09/21/2016

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute dermal toxicity : LD50 (Rat): > 3,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Benzyl alcohol:

Acute oral toxicity : LD50 (Rat): 1,620 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Sodium selenite:

Acute oral toxicity : LD50 (Rat): 4.8 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 0.052 - 0.51 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Skin corrosion/irritation

Not classified based on available information.

Components:

(dl)-a-Tocopheryl acetate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Benzyl alcohol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Sodium selenite:

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 431

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 439

Result : Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sodium Selenite / Vitamin E Injection Formulation

Version 6.0 Revision Date: 11/29/2023 SDS Number: 895430-00016 Date of last issue: 09/30/2023
Date of first issue: 09/21/2016

Components:

(dl)-a-Tocopheryl acetate:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Benzyl alcohol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Method : OECD Test Guideline 405

Sodium selenite:

Result : Irritation to eyes, reversing within 21 days

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

(dl)-a-Tocopheryl acetate:

Test Type : Draize Test
Routes of exposure : Skin contact
Species : Humans
Result : negative

Benzyl alcohol:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Sodium selenite:

Assessment : Probability or evidence of skin sensitization in humans
Remarks : Based on national or regional regulation.

Germ cell mutagenicity

Not classified based on available information.

Components:

(dl)-a-Tocopheryl acetate:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sodium Selenite / Vitamin E Injection Formula-tion

Version 6.0 Revision Date: 11/29/2023 SDS Number: 895430-00016 Date of last issue: 09/30/2023
Date of first issue: 09/21/2016

Method: OECD Test Guideline 473
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

Benzyl alcohol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Sodium selenite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

(dl)-a-Tocopheryl acetate:

Species : Rat
Application Route : Ingestion
Exposure time : 104 weeks
Result : negative

Benzyl alcohol:

Species : Mouse
Application Route : Ingestion
Exposure time : 103 weeks
Method : OECD Test Guideline 451
Result : negative

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sodium Selenite / Vitamin E Injection Formula- tion

Version 6.0 Revision Date: 11/29/2023 SDS Number: 895430-00016 Date of last issue: 09/30/2023
Date of first issue: 09/21/2016

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

(dl)-a-Tocopheryl acetate:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rabbit
Application Route: Ingestion
Result: negative

Benzyl alcohol:

Effects on fertility : Test Type: Fertility/early embryonic development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Mouse
Application Route: Ingestion
Result: negative

Sodium selenite:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Mouse
Application Route: Ingestion
Result: negative

STOT-single exposure

Not classified based on available information.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sodium Selenite / Vitamin E Injection Formulation

Version 6.0 Revision Date: 11/29/2023 SDS Number: 895430-00016 Date of last issue: 09/30/2023
Date of first issue: 09/21/2016

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Components:

Sodium selenite:

Routes of exposure : Ingestion
Assessment : Shown to produce significant health effects in animals at concentrations of 10 mg/kg bw or less.

Repeated dose toxicity

Components:

(dl)-a-Tocopheryl acetate:

Species : Rat
NOAEL : 500 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Benzyl alcohol:

Species : Rat
NOAEL : 1.072 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 28 Days
Method : OECD Test Guideline 412

Sodium selenite:

Species : Rat
NOAEL : 0.88 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Components:

Sodium selenite:

Inhalation : Target Organs: Respiratory Tract
Symptoms: Irritation, Edema
Target Organs: Cardio-vascular system
Symptoms: Lowered blood pressure
Target Organs: Digestive organs
Symptoms: Nausea, Vomiting, Irritability
Ingestion : Target Organs: Nervous system
Symptoms: Neurological disorders
Target Organs: Hair
Symptoms: hair loss

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sodium Selenite / Vitamin E Injection Formulation

Version 6.0 Revision Date: 11/29/2023 SDS Number: 895430-00016 Date of last issue: 09/30/2023
Date of first issue: 09/21/2016

Target Organs: Skin
Symptoms: Rash, Skin disorders
Target Organs: Endocrine system

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

(dl)-a-Tocopheryl acetate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 100 mg/l
Exposure time: 28 d

Toxicity to microorganisms : EC50: > 927 mg/l
Exposure time: 30 min
Method: ISO 8192

Benzyl alcohol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 460 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 230 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 770 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 310 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sodium Selenite / Vitamin E Injection Formulation

Version 6.0 Revision Date: 11/29/2023 SDS Number: 895430-00016 Date of last issue: 09/30/2023
Date of first issue: 09/21/2016

Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 51 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Sodium selenite:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1 - 10 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.2 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Chlamydomonas reinhardtii (green algae)): > 0.1 - 1 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

NOEC (Chlamydomonas reinhardtii (green algae)): > 0.1 - 1 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC (Lepomis macrochirus (Bluegill sunfish)): 0.022 mg/l
Exposure time: 258 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.096 mg/l
Exposure time: 28 d

Toxicity to microorganisms : EC50 (activated sludge): 180 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Persistence and degradability

Components:

(dl)-a-Tocopheryl acetate:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 21.7 - 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

Benzyl alcohol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 92 - 96 %
Exposure time: 14 d

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sodium Selenite / Vitamin E Injection Formulation

Version 6.0 Revision Date: 11/29/2023 SDS Number: 895430-00016 Date of last issue: 09/30/2023
Date of first issue: 09/21/2016

Bioaccumulative potential

Components:

Benzyl alcohol:

Partition coefficient: n-octanol/water : log Pow: 1.05

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.
Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(Sodium selenite)

Class : 9
Packing group : III
Labels : CLASS 9
ERG Code : 171

Marine pollutant : no

Remarks : THE ABOVE INFORMATION ONLY APPLIES TO PACKAGE SIZES WHERE THE HAZARDOUS SUBSTANCE MEETS THE REPORTABLE QUANTITY.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sodium Selenite / Vitamin E Injection Formulation

Version 6.0 Revision Date: 11/29/2023 SDS Number: 895430-00016 Date of last issue: 09/30/2023
Date of first issue: 09/21/2016

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Sodium selenite	10102-18-8	100	8849

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Sodium selenite	10102-18-8	100	8849

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

Components	CAS-No.	Component TPQ (lbs)
Sodium selenite	10102-18-8	10000
Sodium selenite	10102-18-8	100*

*: Solid in the molten or powdered form (particles < 100 microns), in solution, or meeting the NFPA reactivity criteria

SARA 311/312 Hazards : Acute toxicity (any route of exposure)
Respiratory or skin sensitization
Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Sodium selenite 10102-18-8 0.35 - 1.13 %

US State Regulations

Pennsylvania Right To Know

Water	7732-18-5
Polyethylene glycol sorbitan monooleate	9005-65-6
Polyethylene glycol castor oil	61791-12-6
(dl)-a-Tocopheryl acetate	7695-91-2
Benzyl alcohol	100-51-6
Sodium selenite	10102-18-8

California List of Hazardous Substances

Sodium selenite	10102-18-8
-----------------	------------

California Permissible Exposure Limits for Chemical Contaminants

Sodium selenite	10102-18-8
-----------------	------------

The ingredients of this product are reported in the following inventories:

AICS : not determined

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sodium Selenite / Vitamin E Injection Formulation


Version 6.0 Revision Date: 11/29/2023 SDS Number: 895430-00016 Date of last issue: 09/30/2023
Date of first issue: 09/21/2016

DSL : not determined
IECSC : not determined

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	*	3
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)
ACGIH / TWA : 8-hour, time-weighted average
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA Z-1 / TWA : 8-hour time weighted average
US WEEL / TWA : 8-hr TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sodium Selenite / Vitamin E Injection Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/30/2023
6.0	11/29/2023	895430-00016	Date of first issue: 09/21/2016

International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 11/29/2023

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8